



## LAMP ISOFOTON PL



### PHYSICAL AND MECHANICAL CHARACTERISTICS

	ISOFOTON PL 7/12	ISOFOTON PL 11/12	ISOFOTON PL 7/24	ISOFOTON PL 11/24
LENGTH	165 mm			
WIDE	50 mm			
DEPTH	50 mm			
WEIGHT	120 gr	130 gr	120 gr	130 gr

### PROTECTIONS

INVERSE POLARITY PROTECTION	Yes, permanent
SHORT - CIRCUIT PROTECTION	Yes, permanent



## ELECTRICAL CHARACTERISTICS

	ISOFOTON PL 7 / 12	ISOFOTON PL 11 / 12	ISOFOTON PL 7 / 24	ISOFOTON PL 11 / 24
NOMINAL POWER OF THE LAMP	7 W	11 W	7 W	11 W
INPUT NOMINAL VOLTAGE	12 V		24 V	
INPUT VOLTAGE RANGE	10 - 15 V		20 - 30 V	
NOMINAL INPUT CURRENT	0.6 A	0.9 A	0.3 A	0.5 A
COLOUR TEMPERATURE	4.700 K (check others)			
LUMINOSITY AFTER 1000 CYCLES	> 46 lm / W			
WORKING TEMPERATURE RANGE	-10...+50° C			
CATHODE PREHEATING CIRCUIT	Yes			



## CONSTRUCTIVE CHARACTERISTICS

TROPICALIZED CIRCUITS	Yes
SOCKET	E27 (check others)
STROBOSCOPIC EFFECT	No



## OBSERVATIONS

- All specifications are subject to change without prior notice. For fuller details please visit [www.isofoton.com](http://www.isofoton.com)